

Vertical Pallet Strapping Machine

■ Simple Operation

This ergonomically designed machine feeds strap under the pallet, rather than the operator having to reach under the pallet to pull the strap through. The machine is easily operated using the bidirectional lever and start switch.

■ 4-Way Pallet Entry

The bayonet height can be adjusted (10mm, 22.5mm, 35mm or 3/8, 7/8, 1-3/8 in.) by a simple lever. Allows cross strapping through various sized pallet openings.

■ Lower Sealing for Small Pallets

Sealing Point is only 340mm from the floor. Lower pallets can be strapped easily.

■ Versatile Tension Capability

Manual Tension or Automatic Tension are available by means of a simple selector switch.

< Manual Tension Mode >

The strap tension can be controlled manually via the Operation Bar, allowing edge protection to be secured to the pallet prior to strap completion.

< Auto Tension Mode >

Strap tension is applied automatically at a preselected level.



D-53PLT2

Battery operated version is also available.

Standard Specifications

Dimension	Width	2195 mm	86-3/8 in.
	Height	1208 mm	47-1/2 in.
	Depth	542 mm	21-3/8 in.
	Weight	95 kg	211 lbs.
Bayonet Height		10, 22.5, 35 mm	3/8, 7/8, 1-3/8 in.
Package Height		380 mm - free	15 in. - free
Joint / Strap		heat seal / polypropylene ID 200 or 230 X W 200 mm	heat seal / polypropylene 8 in. X 8 in. or 9 in. X 8 in.
Strap		5, 6, 9, 12, (15.5) mm	1/4, 3/8, 1/2 in.
Strap Tension		Max. 690 N (70 kgf)	156 lbf
Power Supply		110, 120, 220, 230, 240V Single phase 50/60Hz 0.4kVA	

Dimensions and specifications are subject to change without notice.

Modification rights reserved.

© 2020 Strapack Corporation

DISTRIBUTED BY:



ISO 9001 and 14001 Certified

STRAPACK CORPORATION
 8-16-6 Ginza, Chuo-ku, Tokyo, 104-0061, JAPAN
 Phone 81-3-6278-1806 Fax. 81-3-6278-1807
 (URL) <http://www.strapack.com> (E-mail) info@strapack.com
 STRAPACK INC.
 33508 Central Avenue, Union City, CA 94587-2097 U.S.A.
 Phone 1-510-475-6000 Fax. 1-510-475-6090
 STRAPACK, N.V./S.A.
 Uilenbaan 200, B-2160 Wommelgem, BELGIUM
 Phone 32-(0)3-355-1520 Fax. 32-(0)3-355-1521